



Welded mesh

The Pantanet® system is a total system, composed of welded galvanised and plastic coated fence on rolls and adapted posts. Ideal for private gardens, parks and farms.

Pantanet®

Benefits

Aesthetic and discrete

High longevity

The wire is galvanised, resistance welded and plastic coated with maximum adhesion. The posts are galvanised inside and outside, passivated and plastic coated, and supplied complete with plastic top caps.

Rapid and fault-free installation

Adapted posts with fixing points guarantee a quick professional installation with an optimal tensioned mesh. Minimal equipment is needed. Two specific posts assortments are available for do-it-yourself installation.

Complete system

Pantanet System is a complete system with a wide range of roll heights, posts and a wide assortment of swing and sliding gates.

Applications

Private gardens
Parks
Schools
Estates
Farms



Mesh

Galvanised mesh, manufactured from galvanised wire, resistance welded and then plastic coated. The horizontal wires show a crimp at every mesh. At 25,4 mm from the top and at the bottom, the mesh is reinforced with a second selvage wire.

Coating

The rolls are made out of galvanised wires. A pre-treatment process guarantees a perfect PVC coating adhesion to the product surface.

Gates

The Pantanet system is totally finished and safely equipped with high-tech gates type Fortinet or Robusta: single and double gates, swing and sliding gates.

Colours

Fence: green 6073, anthracite BF 1016M (Only Pantanet family)

Posts: green RAL 6005, anthracite BF 1016M (Only Pantanet family)

Professional installation

Posts

The straining posts and intermediate posts are equipped with a fixing flange and have a round circular outside profile and are supplied with plastic top caps. The fixing clips are of stainless steel.

Welded Tubular Posts

In and outside galvanised with a min. layer thickness of 275 g/m² (2 sides combined) following Euronorm 10326. Galvanised and plastic coated with polyester with a min. layer thickness of 60 micron.

PANTANET					
Type	Mesh dimensions mm	Diameter wire		Tensile strength of the wire	
		Horizontal mm	Vertical mm	Horizontal	Vertical
Pantanet Protect	50,8 x 50,8	2,50	2,20	400 - 550 N/mm ²	750 - 950 N/mm ²
Pantanet Family	101,6 x 50,8	2,50	2,50	400 - 550 N/mm ²	750 - 950 N/mm ²

ASSORTMENT PANTANET PROTECT & FAMILY										
Total height* mm	Fence mm	Straining posts			Brace posts			Intermediate posts		
		Length mm	Ø mm	Thickness steel plate mm	Length mm	Ø mm	Thickness mm	Length mm	Ø mm	Thickness steel plate mm
1520	1520	2000	48	1,60	2200	38	1,60	2000	48	1,60
1830	1830	2500	60	2,00	2700	38	1,60	2300	48	1,60
2030	2030	2700	60	2,00	2700	38	1,60	2500	48	1,60

Length of rolls: 25 m

Gauteng Sales Office:

082 964 7902

082 839 8889

National Distribution:

KwaZulu Natal: Fenceline (Pty) Ltd:

(031) 705 4322

Southern Cape: Impi Wire: (044) 802 7301

Eastern Cape: Cape Wire: (041) 451 2903



0861 233 623

Head Office:

Berg River Business Park
Cnr Jan van Riebeeck Drive &
Borssenberg Road
Dal Josafat, Paarl, 7646

Postal Address:

P O Box 3356, Paarl, 7620

Phone: +27 (0)21 868 7300

Email: info@betafence.co.za

Website: www.betafence.co.za

