


Product detail



FEATURES & BENEFITS

Trusted protection

Trusted in South Africa to demarcate and protect residential and commercial properties. Two horizontal wires in the panel's bend and 3.65mm wires (4.05 mm when coated) increases its rigidity and protection levels.

Good visibility

Apertures of 50 x 100 mm provide excellent visibility when used with surveillance systems, yet it is too narrow to provide a sturdy foothold which discourages climb-over attempts.

Tamper resistant fixing mechanisms

Expertly designed posts and superior fixing mechanisms maintain the complete installation's integrity and resist attempts to pry panels loose from the post.

Full system 10-year guarantee (standard terms & conditions apply)

Superior coatings underpin our 10-year anti-corrosion guarantee when the full system (panels, Bekafix Secure posts, and stainless steel fixators) is used.

Security level



Applications















Functionalities

Panels



Nylofor Medium's unique feature of two horizontal wires in the reinforcing bends gives the panel extra strength and rigidity when compared to similar products available on the market.


Posts & Fixing Mechanisms



Bekafix® Secure posts are specifically designed and engineered to be used in combination with Betafence's panels. With Bekafix® Secure, the fence is safely tucked behind the lip of the post, withstanding attempts to pry the panel loose. The panels are secured to the post with specialised spider brackets, firmly bolted through the post using M8 stainless steel security bolts and shearoff nuts that protect against tampering.

This combination of Betafence panels with Bekafix post and superior fixing mechanisms delivers a complete fencing system that ensures the installation's integrity and protection levels.

Wire and Apertures



High-strength panels made from 3.65mm core wire, coated to 4.05mm.

Apertures are 50 x 100mm.

Durable High-Quality Coatings

Available as galvanized or Zincalu, with thermoplastic coating in anthracite RAL 7021 or green RAL 6005.

Also available in Zincalu® Super only.

Betafence's highly durable thermoplastic coatings and Zincalu® Super guarantee an extra-long lifespan and low maintenance, delivering superior protection in even the harshest environments.

Optional features



Increase your perimeter's protection by adding sawtooth top rails to further discourage climbing attempts.

Additional Security Accessories

Extended posts and brackets are available to accommodate additional security features such as electric fencing*, flat wrap razor, or BTC coil toppings.

*Supplied and installed by third parties.

Gates

For comprehensive access control solutions that ensure a uniform level of security throughout your perimeter, inquire about our fit-for-purpose range of swing and sliding gates.

Quality Assurance

Our range of high-security products are locally manufactured in our South African ISO 9001:2015 quality certified facility.

NYLOFOR MEDIUM					
Nominal fence height (mm)	Nominal panel width (mm)	Number of reinforcing V bends / panel	Post height (mm)	Number of fixators / panel	Bolts, washers and shear-off nuts / post
1200	2997	2	1600	8	4
1800	2997	3	2400	8	4
2000	2997	4	2700	8	4

SOUTH AFRICA - WESTERN CAPE

Unit B10,

Bergriver Business Park, Paarl, 7646, South Africa

TEL: +27 21 868 7300 info@betafence.co.za

SOUTH AFRICA - GAUTENG

Unit 3,

CDE Premium Park,

Johannesburg, 1685, South Africa

TEL: +27 11 314 8034 info@betafence.co.za





BF-NyloforMedium-231205